

## 90° X 90° SILICON COMPOSITE HYBRID TRACTRIX HORN

Horn loading maximizes efficiency and increases detail while focusing high frequencies towards the listening area. Proprietary Tractrix® geometry provides the most efficient transfer of high frequency waves into the listening area. The phase plug and compressed molded silicon face ensure smooth frequency response. When combined, the cleanest, most natural sound possible is created. The second generation increases horn size for a larger soundstage and enhanced directivity.

## LINEAR TRAVEL SUSPENSION (LTS) TITANIUM DIAPHRAGM TWEETER

The exclusive Linear Travel Suspension minimizes distortion for enhanced, detailed performance. LTS tweeters are a hallmark of previous Reference lines, making it a core component of some of the best speakers in the world.

## VENTED TWEETER DESIGN

The vented tweeter housing reduces standing waves that create unwanted harmonics, resulting in enhanced detail and clarity in high frequency reproduction.

## CERAMETALLIC WOOFERS - ALL NEW DESIGN

A signature feature on the Reference Premiere series, Cerametallic™ woofers are exceptionally rigid and lightweight for minimal distortion and maximum efficiency. New aluminum shorting rings reduce distortion as well as increased power handling and the new motor structure improve transit response with more control with greater speed and accuracy.

## WIDE DISPERSION SURROUND TECHNOLOGY

As the cornerstone of every Klipsch surround speaker, proprietary Wide Dispersion Surround Technology (WDST) provides astounding sonic detail - for lifelike, cinematic sound in any room, even with less-than-ideal placement configurations.

## NEW AND IMPROVED INPUT PANEL

Featuring audiophile-grade wire and easily accessible aluminum binding posts for any connection type.

## FURNITURE GRADE MATERIALS AND FINISHES

Finishes include ebony vinyl and walnut vinyl that boast satin painted baffles with a scratch resistant finish.

## STRONG, FLEXIBLE, REMOVABLE GRILLE

Attaches magnetically for an elegant transition from powerful showstopper to discrete performance piece.



## SPECIFICATIONS

<b>FREQUENCY RESPONSE</b>	62-25kHz +/- 3dB
<b>SENSITIVITY*</b>	94dB @ 2.83V / 1m*
<b>POWER HANDLING (CONT/PEAK)</b>	100W/400W
<b>NOMINAL IMPEDANCE</b>	8 Ohms Compatible
<b>CROSSOVER FREQUENCY</b>	1500Hz
<b>HIGH FREQUENCY DRIVER</b>	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Expanded Tractrix® Horn
<b>LOW FREQUENCY DRIVER</b>	Dual 5.25" Cerametallic Woofers with Faraday rings
<b>ENCLOSURE MATERIAL</b>	MDF (Internally Braced)
<b>ENCLOSURE TYPE</b>	Sealed
<b>INPUTS</b>	Single aluminum binding posts
<b>HEIGHT INCHES (MM)</b>	14.15" (36.0 cm)
<b>WIDTH INCHES (MM)</b>	11.94" (30.3 cm)
<b>DEPTH INCHES (MM)</b>	7.63" (19.4 cm)
<b>PRODUCT WEIGHT LBS (KG)</b>	16.7lb (7.60kg)
<b>FINISH</b>	Ebony, Walnut
<b>ACCESSORIES</b>	Rubber Feet (8)

\*SPL at 1M, half-space anechoic with 2.83V input, in-room sensitivity