



PHONO BOX DS2 USB


Phono preamplifier with HiRes digital USB output

MSRP 549 € (incl. VAT)

Incl. wood side panels MSRP 599 € (incl. VAT)

- · Suitable for MM and MC cartridges
- · Analogue RCA, USB and optical out on back
- 3 Inputs (2 Phono, 1 Line)
- Precise RIAA equalisation
- Dual mono circuitry for optimized channel separation
- Selectable input impedance on front
- Selectable input capacitance on front
- · Digital output sampling frequency adjustable
- · Low noise circuitry
- · Gold-plated RCA in & outputs
- Sandwich alu/metal casing protects from vibrations and electromagnetic interference
- Colour options: silver and black, with optional wooden sidepanels (walnut, rosenut, eucalyptus)

colour options:





Phono input impedance: 10-47kohms Phono capacitance: 100/220/320pF Gain: phono 40/45/50/60/65 dB Inputs: 2 Phono, 1 Line In (RCA)

Outputs: 1 Line Out (RCA), 1 USB B, 1 Optical

Digital output samplingfrequencies: 48/96/192 kHz, DSD

128 (USB only)

Noise floor: 80dbA (40db gain)

THD: < 0,02%

RIAA equalisation curve accuracy: within 0,3dB/20Hz -

20kHz

Trigger in/out: 12V, 2,5mm jack each

Power supply: 18V/500mA DC; 220 - 240V, 50Hz Power consumption: 100 mA DC, < 1 watt standby **Dimensions W x H x D:** 206 x 71 x 226 mm (wood)

240 x 72 x 227 mm (alu)

Weight: 1340g (alu) without power supply 1780g (wood) without power supply



Phono preamplifier for MM/MC cartridges with analogue, digital optic and USB output!

A lot of people already have or plan to buy a very high quality turntable, driven by the fascination of the analogue sound. Many of them also want to record their vinyl in a simple, yet highend way. The Phono Box DS2 USB is the perfect solution. It is a sophisticated phono stage, based on a high end passive/active ultra linear phono equalisation. MM and MC capability as well as extensive variable impedance and capacitance settings allow to match any cartridge, even of highest class for optimum performance. Two individual phono inputs allow you to use two different turntables or

tonearm / cartridge combinations with different sound characteristics to perfectly match your preferred type of music

A very low noise and jitter free A/D converter transfers the analogue signal into high resolution digital format (PCM up to 192kHz or DSD 128). Via its USB output you can record your vinyl on any computer. There is also an analogue line input to digitalize other analogue audio sources. A standard line output to connect the unit to your hifi system isn't missed. The Phono Box DS2 USB is manufactured in a beautiful chassis made out of aluminium and metal, which gives an elegant functional look and avoids the influence of mechanical or electromagnetical interference.



colour option black



black with walnut wood side panels



black with eucalypthus wood side panels



silver with rosewood side panels



silver with walnut wood side panels



silver with eucalypthus wood side panels